


02.02.2023

PP/Steel Loose flanges, ANSI drilled



Product details:

- grey
- Drilled for ANSI B16.5 - 150 lbs d20 - d90 + d450 special ANSI stub flange required
- ANSI B 16.5 150 lbs

Product image for illustration purposes only.

d (mm)	Connection inch (")	Load PN	Load lbs	d2 (mm)	d6 (mm)	D (mm)	b (mm)	k (mm)	Anzahl n	M	kg/piece	Art. No.
20	1/2	10	150	15.9	28	93	12	60.3	4	M12	0.217	013000047
25	3/4	10	150	15.9	33.5	105	12	69.8	4	M12	0.293	013000048
32	1	10	150	15.9	41.5	112	16	79.4	4	M16	0.421	013000049
40	1 1/4	10	150	15.9	50.5	130	16	88.9	4	M16	0.540	013000050
50	1 1/2	10	150	15.9	61.5	132	18	98.4	4	M16	0.551	013000051
63	2	10	150	20	77.5	160	18	120.6	4	M16	0.776	013000052
75	2 1/2	10	150	19	88.5	178	18	139.7	4	M16	1.049	013000053
90	3	10	150	19	107.5	190	18	152.4	4	M16	1.039	013000054
110	4	10	150	19	133	229	18	190.5	8	M16	1.791	013000055
160	6	10	150	22	181.5	279	24	241	8	M20	2.953	013000056
200	8	10	150	22	235.5	342.9	24	298.4	8	M20	4.676	013000057
250	10	10	150	25	293	406	34	362	12	M24	6.201	013000058
315	12	10	150	25.4	337.5	483	34	432	12	M24	11.907	013000059
355	14	10	150	28.6	375.5	540	38	476	12	M24	18.520	013000074
400	16	10	150	28.6	429	597	44	540	16	M27	24.488	013000209
500	20	10	150	31.7	540	708	51	635	20	M27	33.875	010022575

All information provided in respect of technical data shall be considered non-binding. This information does not constitute a guarantee of specific properties or qualities and shall not be construed as a warranty in regard to product condition, durability or service life. Subject to modifications and errors. Our standard terms and conditions apply. For further information, please contact our applications engineering team: pipingsystems@simona.de.